

Web Images Maps News Shopping Gmail more ▼



Sign in

backup different formats into a common format by generating a canonical backup

Advanced Search
Search
Preferences

Web Results 1 - 10 of about 9,900 for backup different formats into a common format by generating a canonical backup log with proprietary name, default values, number of bytes, error numbers, expiration dates (0.29 seconds)

1. (WO/2002/025462) METHOD FOR OBTAINING A RECORD OF DATA BACKUP AND ...

The method of Claim 4, wherein the **number of bytes** for a particular record in the **canonical backup log** comprises a **default value** if the **number of bytes** is ...

www.wipo.int/pctdb/en/wo.jsp?A=US20010249521&WG=-2902025462&DISPLAY=CLAIMS - 38k - [Cached](#) - [Similar pages](#)

2. Network Working Group R. Fielding Request for Comments: 2616 UC ...

Default values are 0 and infinity so that "#element" allows any **number**, The second **format** is in **common** use, but is based on the obsolete RFC 850 [12] ...

www.ietf.org/rfc/rfc2616.txt - 419k - [Cached](#) - [Similar pages](#)

by L. Masinter - [Related articles](#) - [All 3 versions](#)

3. Setting Up the Microsoft DNS Server

If you've maintained zone database files by hand, you might have encoded the **date** in the serial **number**-like 1997102301. This **format** is YYYYMMDDNN, ...

technet.microsoft.com/en-us/library/cc723556.aspx - 86k - [Cached](#) - [Similar pages](#)

4. Glossary

It contains the **name**, serial **number**, **expiration dates**, and public key of a A **common**, text-based **format** for exchanging directory data between systems. ...

download-uk.oracle.com/docs/cd/B14099_19/ldmmanage.1012/b15383/masterglossary.htm - 185k - [Cached](#) - [Similar pages](#)

5. HTTP Working Group R. Fielding, UC Irvine INTERNET-DRAFT J. Gettys ...

The <major> **number** is incremented when the **format** of a message within the protocol The **default value** is q=1. Note: Use of the "q" parameter **name** to ...

www.w3.org/Protocols/HTTP/1.1/draft-ietf-http-v11-spec-rev-06.txt - 444k - [Cached](#) - [Similar pages](#)

6. Mapping interface for a distributed server to translate between ...

Additionally, the total **number** of connections **into** the database can be A "token" is an item added to a **value** in a file to describe the **format** of the ...

www.freepatentsonline.com/6199068.html - [Similar pages](#)

by RC Carpermer - 2001 - [Cited by 21](#) - [Related articles](#) - [All 3 versions](#)

7. IBM Globalization - Terminology - terms M and N

This allows you to **format** the same data differently on **different** screen (2) Pertains to the **number of bytes** of storage that can be stored on the ...

www-01.ibm.com/software/globalization/terminology/mn.jsp - 396k - [Cached](#) - [Similar pages](#)

8. [PDF] Seafarers' Identity Documents Convention (Revised), 2003 (No. 185)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

Expiration date æ SID **date** of expiry in seconds since epoch (SSE) **format**

Value. Comment. Unenrolled finger record (4 **bytes** only). Finger **number** ...

[www.ilo.org/public/english/dialogue/sector/papers/maritime/sid0002.pdf](#) - [Similar pages](#)

9. [\[PDF\] BackupReport Plug-in Guide for Openview OmniBack II](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

ber of **backup** products. To provide cross-vendor consistency, a **common data format** is **Bytes** is the **number of bytes** backed up by a given **backup** job. ...


[support.bocada.com/content/downloads/v4.0.1/docs/OmniBackPlugInGuide401.pdf](#)

- [Similar pages](#)

10. [Gammadyne Mailer Revision History Version 33.1 \(9/22/2008\) ...](#)

Added to the end of the Incoming **Log** statistics on the **number** of criteria Added the "**Default date format**" and "**Default time format**" settings to the ...

[gammadyne.com/mmail-rh.txt](#) - 168k - [Cached](#) - [Similar pages](#)



[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#) | [Try Google Experimental](#)